

CLAIMS

I claim:

1. An apparatus comprising:

a base;

an extension attached to the base;

a first package having an enclosure attached to a backing, wherein the first package has a depth;

a second package having an enclosure attached to a backing, wherein the second package has a depth which is the same as the first package;

and wherein the first package and the second package can be placed on the extension so that the enclosure of the first package is adjacent to the enclosure of the second package and the length taken up by the first and second packages along the extension is about the depth of the first package.

2. The apparatus of claim 1 wherein

the length taken up by the first and second packages along the extension is approximately equal to the depth of the first package plus the depth of the backing of the second package.

3. The apparatus of claim 1 wherein

the first package can be placed on the extension so that the first package will not substantially rotate.

4. The apparatus of claim 3 wherein

the extension has an elongated cross section; and
wherein the backing of the first package has a slot with an elongated opening into which
the extension can be inserted

5. The apparatus of claim 1 wherein

the extension projects downwards from the base and gradually curves upwards.

6. A method comprising the steps of

forming a package having an enclosure attached to a backing, wherein the package has a
top and a bottom;

forming a first slot in the top of package;

forming a second slot in the bottom of the package; and

creating a hook with a penetrating end which can penetrate both the first and the second
slots.

7. The method of claim 6 further comprising

hanging the hook on a wall.

8. The method of claim 7 further comprising

hanging the package on the hook.

9. A method comprising:

forming a hook comprised of an extension attached to a base;

forming a first package having an enclosure attached to a backing, wherein the first package has a depth;

forming a second package having an enclosure attached to a backing, wherein the second package has a depth which is the same as the first package;

and wherein the first package and the second package can be placed on the extension so that the enclosure of the first package is adjacent to the enclosure of the second package and the length taken up by the first and second packages along the extension is about the depth of the first package.

10. The method of claim 9 wherein

the length taken up by the first and second packages along the extension is approximately equal to the depth of the first package plus the depth of the backing of the second package.

11. The method of claim 9 wherein

the first package can be placed on the extension so that the first package will not substantially rotate.

12. The method of claim 11 wherein

forming the extension so it has an elongated cross section; and

forming a slot with an elongated opening in the backing of the first package into which the extension can be inserted

13. The method of claim 9 wherein

the extension projects downwards from the base and gradually curves upwards.